



 **Mactronic®**

25 lat
AUTORYZOWANY
PARTNER
STREAMLIGHT®



Streamlight® was founded 50 years ago in 1973. She initiated spectacular development of the lighting industry. Streamlight® Inc., headquartered in the USA, in Eagleville, Pennsylvania, is a manufacturer of durable flashlights designed to meet the expectations of demanding customers. Over the years, Streamlight® has set new trends in the industry. Launched iconic products: Fire Vulcan® LED searchlights, legendary TLR mounted on weapons, tactical Sidewinders mounted on helmets and leading on Survivor® Rechargeable Angle Flashlight.

On the Polish market, a representative and partner of Streamlight® for over Mactronic® Group Sp. z o.o., the largest supplier of flashlights in Poland. As an authorized Streamlight® Distributor and Service Center in Poland, it offers a wide range of products, short delivery times, professional trained assistance by Streamlight servicemen. It also provides quick access to spare parts, accessories, product warranty, and protection.

Firma Streamlight® została założona 50 lat temu, w 1973 roku. Zapoczątkowała spektakularny rozwój branży oświetleniowej. Streamlight® Inc., z siedzibą w USA, w miejscowości Eagleville, w stanie Pensylwania jest producentem trwałych latarek zaprojektowanych tak, aby spełniały oczekiwania wymagających klientów. Przez lata Streamlight wyznaczał nowe trendy w branży. Wprowadził na rynek kultowe produkty: szperacze Fire Vulcan® LED, legendarne TLR montowane na broni, taktyczne Sidewindery montowane na hełmach i wiodąca na świecie latarka kątowna Survivor® z możliwością ładowania.

Na rynku polskim przedstawicielem, a zarazem partnerem Streamlight od ponad 25 lat jest firma Mactronic® Group Sp. z o.o., największy dostawca latarek w Polsce. Jako autoryzowany Dystrybutor i Centrum Serwisowe Streamlight w Polsce, oferuje szeroką gamę produktów, krótkie terminy dostaw, fachową pomoc przeszkolonych przez Streamlight® serwisantów. Zapewnia także szybki dostęp do części zamiennych, akcesoriów oraz gwarancję i ochronę produktu.



Survivor® ATEX

L-90562



175 lm

405 m



ATEX: FTZU 15 ATEX 0046X; IEC Ex FTZU 15.0029X,
II 1G Ex ia op is IIB T3/T4 Ga;
II 2G Ex ia op is IIC T3/T4 Gb

LIGHT SOURCE	White C4® LED	
POWER	Li-Ion 1500 mAh	
	LUMENS	RUN TIME
HIGH	175 lm	3 h 30 min
LOW	60 lm	10 h
DIMENSIONS	179 x 72 x 58 mm	
WEIGHT	388 g	
THE SET INCLUDES	Li-Ion battery 6,2V, charging base, 12V DC cord, 230V AC cord	

IP66
STANDARD

2 m SHOCK
RESISTANT



Survivor® X ATEX

L-90971, L-90973



250 lm

447 m



ATEX: II 1G Ex ia op is IIC T3/T4 Ga; II 1D Ex ia op is IIIC T135° Da
(IECEX: Ex ia op is IIC T3/T4 Ga; Ex ia op is IIIC T135° Da
NFPA 1971-8.6 (2013) - latarka
NFPA 1901-14.1.10.2 (2016) - latowarka

LIGHT SOURCE	White LED		
POWER	Li-Ion 2600 mAh		
	LUMENS	CANDELAS	RUN TIME
HIGH	250 lm	50000 cd	4 h
LOW	60 lm	14000 cd	15 h
DIMENSIONS	172 x 72 x 58 mm		
WEIGHT	346 g		
THE SET INCLUDES	L-90971: flashlight L-90973: Li-Ion battery, charging base, 12V DC cord, 230V AC cord		

IP67
STANDARD

2 m SHOCK
RESISTANT



Portable Scene Light® II

L-46001



10000 lm



LIGHT SOURCE	18 x C4® LED	
POWER	2 x Li-Ion 5200 mAh	
	LUMENS	RUN TIME
HIGH	10000 lm	2 h
MEDIUM 1	8300 lm	2,75 h
MEDIUM 2	6300 lm	3,75 h
LOW 1	4500 lm	5,75 h
LOW 2	2300 lm	11 h
DIMENSIONS	40,6 x 28,9 x 30,5 cm	
WEIGHT	6,10 kg	
THE SET INCLUDES	12V DC cord, 230V AC cord	

IPX7
STANDARD

Portable Scene Light® / Ext

L-45681, L-45671



5300 lm

410 m



LIGHT SOURCE	6 x C4® LED	
POWER	Li-Ion 14 400 mAh	
	LUMENS	RUN TIME
HIGH	5300 lm	4 h
MEDIUM	2500 lm	9 h
LOW	1300 lm	18 h
DIMENSIONS L-45671	57,2 x 27,9 x 17 cm	
WEIGHT L-45671	11,3 kg	
DIMENSIONS L-45681	64,8 x 27,9 x 17 cm	
WEIGHT L-45681	11,6 kg	
THE SET INCLUDES	L-45671: 12V DC cord, 230V AC cord, L-45681: 230V AC cord	

IP67
STANDARD

Vulcan® 180 HAZ-LO ATEX

L-44342



400 m 316 lm

ATEX: II 1G Ex ia T4 Gb; IECEx: Ex ia IIC T4 Gb;
DEMKO 19 ATEX 2307X; IECEx UL 19.0115x

LIGHT SOURCE	3 x White LED	
POWER	Li-Ion 10 350 mAh	
	LUMENS	RUN TIME
HIGH	400 lm	10 h
LOW	130 lm	24 h
DIMENSIONS	length 18,8 cm	
WEIGHT	1,12 kg	
THE SET INCLUDES	shoulderstrap, charging base, 12V DC cord, 230V AC cord	



Vulcan Clutch®

L-44362, L-44365, L-44360



520 m 1700 lm

LIGHT SOURCE	3 x White LED		
POWER	Li-Ion 5200 mAh		
	LUMENS	LIGHT RANGE	RUN TIME
HIGH	1700 lm	520 m	6,5 h
LOW	380 lm	245 m	18h
FLASH	n/a	n/a	25 h
DIMENSIONS	23,85 x 11,68 x 16,26 cm		
WEIGHT	1288 g		
THE SET INCLUDES	L-44362: 230V AC/12V DC cord L-44365: 12V DC cord		



BearTrap®

L-61521

 **STREAMLIGHT**

 174 m

 2000 lm



LIGHT SOURCE	White LED		
POWER	Li-Ion 5200 mAh		
	LUMENS	LIGHT RANGE	RUN TIME
	FLOOD		
HIGH	2000 lm	69 m	2,5 h
MEDIUM	1000 lm	52 m	5 h
LOW	575 lm	38 m	8,75 h
	SPOT		
HIGH	1000 lm	174 m	4,5 h
MEDIUM	450 lm	120 m	8,75 h
LOW	325 lm	100 m	12,5 h
DIMENSIONS	length 19,35 cm		
WEIGHT	992,23 g		
THE SET INCLUDES	AC charger, 120V AC cord, 12V DC charger, 240V AC (AUS/NZ), Li-Ion battery		

 IPX4 STANDARD

 1 m SHOCK RESISTANT

Enduro® PRO HAZ-LO® ATEX

L-61428

 **STREAMLIGHT**



 73 m

 235 lm

ATEX: II 1G Ex ia op is IIC T4 Ga - FTZU 18 ATEX 0101X
IECEx: Ex ia op is IIC T4 Ga - IECEx FTZU 19.0003X
INMETRO: Ex ia op is IIC T4 Ga - DNV 20.0025 X



POWER	3 x AAA	
	LUMENS	RUN TIME
SPOT/FLUOD COMBO	235 lm	4,75 h
SPOT	160 lm	5 h
FLUOD	160 lm	5 h
DIMENSIONS	length 5,56 cm	
WEIGHT	99,2 g	
THE SET INCLUDES	3 x AAA batteries	

 IPX7 STANDARD

 2 m SHOCK RESISTANT

POWER	Li-Ion	
	LUMENS	RUN TIME
SPOT/FLOOD COMBO	275 lm	5,5 h
SPOT	180 lm	7,25 h
FLOOD	105 lm	13,5
DIMENSIONS	length 17,78 - 19,35 cm	
WEIGHT	192,78 - 201 g	
THE SET INCLUDES	Li-Ion battery	

 IP67 STANDARD  2 m SHOCK RESISTANT



Stinger® 2020
L-44362, L-44365, L-44360

POWER	SL-B26 Battery Pack		
	LUMENS	LIGHT RANGE	RUN TIME
HIGH	2000 lm	315 m	2 h
MEDIUM	850 lm	200 m	4 h
LOW	100 lm	70 m	24 h
STROBE	n/a	n/a	3,25 h
DIMENSIONS	length 19,48 cm		
WEIGHT	348,70 g		
THE SET INCLUDES	Li-ion battery		

 IPX7 STANDARD  2 m SHOCK RESISTANT





25 lat
AUDYTOWANY
PARTNER
STREAMLIGHT

Mactronic® Group Sp. z o.o.
ul. Stargardzka 4,
54-156 Wrocław, Poland

T: +48 71 351 86 53

F: +48 71 358 44 42

biuro@mactronic.pl

mactronic.pl

